



NOTICE TO BIDDERS

Notice is hereby given that sealed bids will be received by the Board of Sully County of Sully County, South Dakota, 700 Ash Avenue, until 9:00 a.m. on the 5th day of November, 2026, for the purchase 2 Truck Boxes with Kybato systems.

ALL BIDS MUST BE SEALED AND MARKED: **“TRUCK BOXES”**.

Such bids will be publicly opened and read aloud at the Sully County Courthouse, 700 Ash Avenue, Onida, South Dakota at the time specified on the Call for Bids. If due to inclement weather the regular meeting is postponed, bid opening will be held at the following meeting of the Sully County Commissioners.

Specifications and bidding documents are available at www.sully.sdcounty.gov, on file at the Sully County Highway Department, 812 Cherry Avenue or at the Sully County Auditor's Office, 700 Ash Avenue, Onida, SD 57564. For questions and comments please contact Highway Superintendent JJ Schall at (605) 222-2623.

The Board reserves the right to reject any or all bids, and to waive defects or informalities if deemed in the best interest of Sully County to do so.

**SULLY COUNTY HIGHWAY DEPARTMENT
TRUCK BOX BID DOCUMENT**

BID OPENING DATE: November 5, 2026

QUANTITY: 2 systems will be purchased from the winning bid

BID SPECIFICATIONS:

1. Kybato System mounted with 1 subframe
2. Subframe, each bare, with 6 hooks
3. Galion Dump Body installed on subframe
 - Body will 16 foot in length, side height of 42 inches, tailgate height of 50", front headsheet height of 64", inside width of 84" and outside width of 96".
 - Floor, headsheet and tailgate will be constructed with 7 GA AR500.
 - Sides will be constructed with 10 GA AR500 with Galion style horizontal V-Bend for bracing.
 - Capacity of body to minimum of 14.5 cubic yards.
 - Two complete body prop assemblies.
 - Crossmemberless design with 11" formed longsill made with 7 GA 100K.
 - 22" front board gusset to extend from top of wall to cabshield, 8" rear board gusset.
 - Two 6" ovals in rear posts cut in at the highest point possible and two additional 6" ovals cut in for strobe lights.
 - Must be six panel tailgate and have air operated tailgate latches.
 - 10 GA steel cabshield, 13" deep and 84" wide.
 - 2.5" round holes cut in face of cabshield facing forward.
 - Body to be 100% continuously welded.
 - No posts for front of body.
 - Body to have sloped tailgate.
 - Tarp friendly cast tailgate hardware.
 - Casting lower tailgate hardware.
 - To include 3/8" Grade 70 tailgate chains.
 - One outside step located on driverside with grab handle and ladder.
 - Hoist to be a trunnion mounted Mailhot G4 150-5.7-4.
 - Tarp rail to extend the length of body on both sides. Tarp rail to constructed of 3/8" X 1 1/2" flatbar.
 - Body to be Wheelabrated, Zinc Primered and Powder Coated Black.
4. Fifth Wheel – Sliding
5. Dump Body painted to match truck cab.

Bid Amount for Two (2) Systems: \$_____

Bidder Certification

The undersigned bidder certifies that the bid submitted herein complies with the specifications listed above and agrees to furnish two (2) complete systems as described, in accordance with the terms and condition established by the Sully County Highway Department.

Signature

Date

Printed Name

Company